



ARDEX Bonding Primer

Solvent Based Primer

ARDEX Bonding Primer

Solvent Based Primer

DESCRIPTION

Bonding Primer solvent based primer is designed to lock particles on the substrate to achieve maximum adhesion. It has excellent durability and is a low viscosity binder that seals absorbent substrates and penetrates dust.

TYPICAL APPLICATIONS

- New and old concrete
- Timber
- Compressed fibreboards
- Primer for acrylic coatings

APPLICATION REQUIREMENTS

General

Do not apply Bonding Primer if the temperature is below 5°C or above 35°C.

Substrate preparation

The surface to be coated should be dry, clean, sound and free from oil, grease and flaking paint. New concrete should be left a minimum of 28 days before application commences. All cracks or holes exceeding 2mm are to be repaired before application commences.

APPLICATION SPECIFICATION

Apply with brush, long nap roller or conventional spray. Ensure that the coating is applied evenly at the recommended coverage rates. Allow a drying time of at least one hour.

COVERAGE

Approximately 5-8m²/litre on horizontal and vertical surfaces.

PACKAGING

20L Metal Pails.

CLEAN UP

Clean all equipment in general purpose thinners immediately after use.

STORAGE

Bonding Primer must be stored above 6°C.

SHELF LIFE

One year in unopened containers stored at 20°C.

SAFETY DIRECTIONS

Avoid contact with skin and inhalation of the vapour. Provide adequate ventilation. Keep out of reach of children. If swallowed contact a doctor or Poisons Information Centre.

Contact Ardex for specific applications and material safety data sheet.