



ARDEX AF 675

Vinyl Skirting Contact Adhesive

Strong Ultimate Bond - Long Term Reliability

Solvent Based - Installs Fast

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX AF 675

Vinyl Skirting Contact Adhesive

DESCRIPTION

ARDEX Contact Vinyl Skirting Adhesive is designed for fixing vinyl skirting to plasterboard, timber or metal.

APPLICATION

Internal permanent installation of vinyl skirting.

IN THE ARDEX SYSTEM

To ensure enhanced performance, reliability and warranty always use ARDEX adhesives within SYSTEMARDEX. Other SYSTEMARDEX products include:

- ARDEX Moisture Barrier
- ARDEX Concrete Sealer
- ARDEX Substrate Primers
- ARDEX Self Levelling and Smoothing Compounds
- ARDEX Finishing Compounds

SURFACE PREPARATION

All substrates must be structurally sound, level, protected from moisture, free from dust, oil, dirt and contaminants.

Contact ARDEX Technical Services for other substrates including terrazzo, ceramic tiles and metal substrates.

DIRECTIONS FOR USE

Refer to floor covering manufacturer's instructions. Condition adhesive and covering to working area temperature 24 hours prior to and 48 hours after installation.

Installation temperature of working area and substrate to be a minimum of 10°C and a maximum of 30°C.

Apply an even coat of adhesive to both surfaces by brush or roller. On porous surfaces a second application may be required. Allow adhesive to touch dry. Align covering then press or roll to complete bond. Full strength will not be achieved for 24 hours.

NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with Federal, State and Local waste disposal regulations. Do not flush adhesive down drains.

SAFETY PRECAUTIONS

RISK

R11 Highly flammable
R20 Harmful by inhalation
R38 Irritating to skin

DO NOT SWALLOW

S24125 Avoid contact with skin and eyes
S36137 Wear suitable protective clothing and gloves
S23 Do not breathe vapour or spray mist
5 51 Use only in well ventilated area
S3/9 Keep in cool well ventilated place
S16 Keep away from ignition sources - No smoking
S33 Take precautionary measures against static discharges

FIRE

Use foam, dry chemical or carbon dioxide to extinguish fire. Firefighters should wear full protective clothing and self contained breathing apparatus. Material Safety Datasheet is Available upon request from the ARDEX website www.ardex.com or request from point of sale.

FIRST AID

If swallowed, do NOT induce vomiting. If inhaled exit from contaminated area. Apply artificial respiration if not breathing.

In case of contact with eyes, wash out immediately with plenty of water. If irritation persists contact a doctor or Poisons Information Centre.

If skin contact occurs, remove contaminated clothing and wash skin with running water.

For advice or in case of accident contact Poisons Information Centre (Australia Ph: 13 1126; New Zealand 0800 764 766) or a doctor immediately.

TECHNICAL PROPERTIES

Colour: Light yellow

Coverage: 3-4 m²/L

Packaging: 4 litre container

Shelf Life: One year from date of manufacture in unopened container stored at 23°C and 50% RH

ARDEX Australia Pty Ltd

NSW Ph (02) 9851 9100 Fax (02) 9838 7970
QLD Ph (07) 3817 6000 Fax (07) 3881 3188
VIC/TAS Ph (03) 9308 9255 Fax (03) 9308 9332
SA Ph (08) 8268 2511 Fax (08) 8345 3207
WA Ph (08) 9256 8600 Fax (08) 9455 1227

ARDEX New Zealand Ltd

Christchurch Ph (03) 3843 029 Fax (03) 3849 779
Auckland Ph (09) 2967 690 Fax (09) 2967 689
Wellington Ph (04) 5685 949 Fax (04) 5686 376

Technical Services Toll Free: 1800 224 070

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2008.

All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.