



MAX PREP

FEATHER-IT

Finish Coat and Smoothing Compound



Rapid drying | Install floor coverings after 30 minutes

Easy to install | Feather to 3mm in one application

Coverage | 10kg bag covers 30m² as a skim coat

PRODUCT USE

MJS Max Prep Feather-It provides a smooth finish coat for various substrates that will receive a floor covering. MJS Feather-It allows for installation of most floor coverings in as little as 30 minutes on suitable substrates like concrete, wood, ceramic and quarry tile without a primer. It is suitable for residential and light commercial areas.

BEFORE INSTALLATION

Concrete floors must be structurally sound, clean and free of dirt, dust, oil, curing and sealing compounds and any other surface contaminant which may act as a bond breaker. Where required, mechanically clean the floor using recommended preparation methods such as shotblasting, scarifying, diamond grinding, shaving or other acceptable methods to a suitable surface. Acid etching is not an acceptable method of cleaning the subfloor. Do not use solvents or sweeping compounds. Subfloor temperatures must be a minimum of 10°C.

HOW TO MIX

Depending on site conditions, applicators preference and the finished surface requirements 4.5–5.0L of water to 10kg of

powder. MJS Max Prep repair products react and harden quickly when mixed with water. Thorough mixing in the shortest possible time is essential to ensure a lump free, slump resistant mortar. Always mix the powder into the water. Mechanical mixing using a mixing paddle and electric drill will produce a creamier, smoother consistency. Do not overwater.

HOW TO INSTALL

MJS Feather-It is easily applied to any prepared surface using a steel trowel. Apply sufficient pressure to fill all defects and to fine the product into the subfloor surface. It is not necessary to leave a minimum thickness on the substrate. Use the least amount possible to obtain the desired smoothness.

THICKNESS

MJS Feather-It can be applied from a true fine edge up to 3mm in one application.

POT LIFE

Approximately 18 minutes at 23°C.

INSTALLATION OF FLOORING

As soon as the MJS Feather-It can be walked on without damaging the surface (approx 30 minutes), floorcoverings such as vinyl, carpet

and ceramic tile can be installed. When installing a skim coat of MJS Feather-It over non-porous surfaces such as ceramic tiles or vinyl, always refer to the adhesive supplier for their recommended installation procedure.

COVERAGE

As a concrete skim coat up to 30m² can be achieved and even more over plywood. At 1mm 20m² can be achieved over concrete.

STORAGE

MJS Feather-It has a shelf life of 12 months if stored in dry conditions in unopened packaging.

HEALTH & SAFETY

MJS Feather-It contains Portland cement. Avoid generation of dust. Do not inhale dust. Avoid contact with eyes or skin. Wear suitable protective gloves and safety glasses. In case of contact with eyes, rinse opened eye for several minutes under running water. In case of contact with skin, rinse affected areas thoroughly with running water. If dust is inhaled, remove to fresh air, ensure breathing passages are clear, and rinse mouth with running water. If symptoms persist, seek medical advice.



MAX PREP

CONTACT

QLD

Mansfield (07) 3347 7300

Townsville (07) 4727 6500

Bowen Hills (07) 3514 5700

Burleigh (07) 5586 9800

Cairns (07) 4245 8300

Mackay (07) 4864 3500

Maroochydore (07) 5475 8100

Toowoomba (07) 4592 4700

NSW

Wetherill Park (02) 9616 1500

Newcastle (02) 4965 2600

Seven Hills (02) 8672 2100

Tamworth (02) 0407 454 500

ACT

Fyshwick (02) 6212 9400

VIC

Sunshine (03) 9351 7400

Dandenong (03) 8780 6900

SA

Adelaide (08) 8178 5300

TAS

Hobart (03) 6242 8800

NT

Darwin (08) 7922 9700

DISCLAIMER

The technical details, recommendations and other information contained in this data are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.