

Ardex WR Prime Ardex (Ardex Australia)

Chemwatch Hazard Alert Code: 2

Issue Date: **03/09/2020** Print Date: **12/07/2021** S.GHS.AUS.EN

Chemwatch: **5396-80**Version No: **3.1.8.8**

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier		
Product name	Ardex WR Prime	
Chemical Name	Not Applicable	
Synonyms	Not Available	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Universal additive and primer for renders and adhesives.

Details of the supplier of the safety data sheet

Registered company name	Ardex (Ardex Australia)	
Address	20 Powers Road Seven Hills NSW 2147 Australia	
Telephone	1800 224 070	
Fax	1300 780 102	
Website	www.ardexaustralia.com	
Email	technicalservices@ardexaustralia.com	

Emergency telephone number

Association / Organisation	Ardex (Ardex Australia)	
Emergency telephone numbers	1800 224 070 (Mon-Fri, 9am-5pm)	
Other emergency telephone numbers	Not Available	

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings

	Min	Max	
Flammability	0		
Toxicity	0		0 = Minimum
Body Contact	1		1 = Low
Reactivity	0		2 = Moderate
Chronic	2		3 = High 4 = Extreme

Poisons Schedule	Not Applicable
Classification [1]	Skin Sensitizer Category 1, Eye Irritation Category 2A
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Ardex WR Prime

Issue Date: **03/09/2020**Print Date: **12/07/2021**

Hazard pictogram(s)



Signal word	Warning

Hazard statement(s)

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P261	Avoid breathing mist/vapours/spray.	
P264	Wash all exposed external body areas thoroughly after handling.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
65405-61-0	10-30	styrene acrylate copolymer
9003-55-8	10-30	styrene/ butadiene copolymer
2682-20-4	<1	2-methyl-4-isothiazolin-3-one
Not Available	>60	Ingredients determined not to be hazardous
Legend:	Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should

Chemwatch: **5396-80**Version No: **3.1.8.8**

Page 3 of 9 Ardex WR Prime

Issue Date: **03/09/2020**Print Date: **12/07/2021**

take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances. In such an event consider:

foam.

Special hazards arising from the substrate or mixture

oposial nazarao anomy nom mo outourae or mixture			
Fire Incompatibility	None known.		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. 		
Fire/Explosion Hazard	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. 		
i ile/Lapiosion Hazaru	Decomposes on heating and produces toxic fumes of: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.		
HAZCHEM	Not Applicable		

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Ardex WR Prime	Not Available	Not Available	Not Available

Ardex WR Prime

Issue Date: **03/09/2020**Print Date: **12/07/2021**

Ingredient	Original IDLH	Revised IDLH
styrene acrylate copolymer	Not Available	Not Available
styrene/ butadiene copolymer	Not Available	Not Available
2-methyl-4-isothiazolin-3-one	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
2-methyl-4-isothiazolin-3-one	D	> 0.01 to ≤ 0.1 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection











Eve and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- ► Wear safety footwear or safety gumboots, e.g. Rubber

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective

Hands/feet protection

- equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care.

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- ► Barrier cream
- Skin cleansing cream.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Ardex WR Prime

Material	СРІ
BUTYL	A
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PE	С
PE/EVAL/PE	С
PVA	С
PVC	С
TEFLON	С
VITON	С

- * CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

Respiratory protection

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001. ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	BAX-AUS / Class1 P2	-
up to 50	1000	-	BAX-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	BAX-2 P2
up to 100	10000	-	BAX-3 P2
100+			Airline**

- * Continuous Flow ** Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)
 - Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
 - ▶ The wearer must be warned to leave the contaminated area immediately on

Chemwatch: **5396-80**Version No: **3.1.8.8**

Ardex WR Prime

Issue Date: **03/09/2020**Print Date: **12/07/2021**

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

- * Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.
- detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Appearance	Liquid; mixes with water.		
	'		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Inges

Information on toxicological effects

Inhaled The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product

stion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of
Stion	corroborating animal or human evidence

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Skin Contact Irritation and skin reactions are possible with sensitive skin

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).

Chronic Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Ardex WR Prime	TOXICITY	IRRITATION
	Not Available	Not Available

Ardex WR Prime

Issue Date: 03/09/2020 Print Date: 12/07/2021

styrene acrylate copolymer	TOXICITY	IRRITATION
	Not Available	Not Available
	TOXICITY	IRRITATION
styrene/ butadiene copolymer	Dermal (rabbit) LD50: >20000 mg/kg ^[2]	Eye (rabbit) 500: mg/24h -
	Oral(Rat) LD50; 71000 mg/kg ^[2]	Eye: Mild
	TOXICITY	IRRITATION
		induitation.
	dermal (rat) LD50: 242 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]
2-methyl-4-isothiazolin-3-one		
2-methyl-4-isothiazolin-3-one	dermal (rat) LD50: 242 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

STYRENE/ BUTADIENE COPOLYMER

Version No: 3.1.8.8

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important.

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.

2-METHYL-4-ISOTHIAZOLIN-3-ONE

Based on laboratory and animal testing, exposure to the material may result in irreversible effects and mutations in humans. In light of potential adverse effects, and to ensure a harmonised risk assessment and management, the EU regulatory framework for biocides has been established with the objective of ensuring a high level of protection of human and animal health and the environment. To this aim, it is required that risk assessment of biocidal products is carried out before they can be placed on the market. A central element in the risk assessment of the biocidal products are the utilization instructions that defines the dosage, application method and amount of applications and thus the exposure of humans and the environment to the biocidal substance.

Humans may be exposed to biocidal products in different ways in both occupational and domestic settings. Many biocidal products are intended for industrial sectors or professional uses only, whereas other biocidal products are commonly available for private use by non-professional users. No significant acute toxicological data identified in literature search.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Formaldehyde generators (releasers) are often used as preservatives. The maximum authorised concentration of free formaldehyde is 0.2% and must be labelled with the warning sign "contains formaldehyde" where the concentration exceeds 0.05%. The use of formaldehyde-releasing preservatives ensures that the level of free formaldehyde in the products is always low but sufficient to inhibit microbial growth - it disrupts metabolism to cause death of the organism. However there is a concern that formaldehyde generators can produce amines capable of causing cancers (nitrosamines) when used in formulations containing amines.

NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.

Considered to be a minor sensitiser in Kathon CG (1) (1). Bruze et al - Contact Dermatitis 20: 219-39, 1989

STYRENE/ BUTADIENE **COPOLYMER & 2-METHYL-**4-ISOTHIAZOLIN-3-ONE

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	X
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	X

Legend:

★ - Data either not available or does not fill the criteria for classification

- Data available to make classification

SECTION 12 Ecological information

Toxicity

Ardex WR Prime	Endpoint Not Available	Test Duration (hr) Not Available	Species Not Available	Value Not Available	Source Not Available
styrene acrylate copolymer	Endpoint Not Available	Test Duration (hr) Not Available	Species Not Available	Value Not Available	Source Not Available

Chemwatch: **5396-80**Version No: **3.1.8.8**

Ardex WR Prime

Issue Date: **03/09/2020** Print Date: **12/07/2021**

	Endpoint	Test Duration (hr)	Species		Value	Source
styrene/ butadiene copolymer	Not Available	Not Available	Not Available		Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Valu	ie	Source
	LC50	96h	Fish	0.08	31-0.122mg/L	4
2-methyl-4-isothiazolin-3-one	EC50	48h	Crustacea	0.18	89-0.257mg/L	4
	NOEC(ECx)	96h	Algae or other aquatic plants	0.01	mg/l	2
	EC50	96h	Algae or other aquatic plants	0.06	63mg/l	2
Legend:	V3.12 (QSAR) -	IUCLID Toxicity Data 2. Europe ECHA Regisi Aquatic Toxicity Data (Estimated) 4. US EPA, I apan) - Bioconcentration Data 7. METI (Japan)	Ecotox database - Aquatic Toxicity Data 5.			

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2-methyl-4-isothiazolin-3-one	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
2-methyl-4-isothiazolin-3-one	LOW (LogKOW = -0.8767)

Mobility in soil

Ingredient	Mobility
2-methyl-4-isothiazolin-3-one	LOW (KOC = 27.88)

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- Product / Packaging disposal
- Recycle wherever possible.
 Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
styrene acrylate copolymer	Not Available
styrene/ butadiene copolymer	Not Available
2-methyl-4-isothiazolin-3-one	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
styrene acrylate copolymer	Not Available
styrene/ butadiene copolymer	Not Available
2-methyl-4-isothiazolin-3-one	Not Available

Issue Date: **03/09/2020** Print Date: **12/07/2021**

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

styrene acrylate copolymer is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

styrene/ butadiene copolymer is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

2-methyl-4-isothiazolin-3-one is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (styrene acrylate copolymer; styrene/ butadiene copolymer; 2-methyl-4-isothiazolin-3-one)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (styrene acrylate copolymer; styrene/ butadiene copolymer)
Japan - ENCS	No (styrene acrylate copolymer)
Korea - KECI	No (styrene acrylate copolymer)
New Zealand - NZIoC	No (styrene acrylate copolymer)
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	No (styrene acrylate copolymer)
Mexico - INSQ	No (styrene acrylate copolymer)
Vietnam - NCI	Yes
Russia - FBEPH	No (styrene acrylate copolymer)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	03/09/2020
Initial Date	30/04/2020

SDS Version Summary

Version	Date of Update	Sections Updated
2.1.1.1	30/04/2020	Ingredients
3.1.1.1	03/09/2020	Classification change due to full database hazard calculation/update.
3.1.2.1	26/04/2021	Regulation Change
3.1.3.1	03/05/2021	Regulation Change
3.1.4.1	06/05/2021	Regulation Change
3.1.5.1	10/05/2021	Regulation Change
3.1.5.2	30/05/2021	Template Change
3.1.5.3	04/06/2021	Template Change
3.1.5.4	05/06/2021	Template Change
3.1.6.4	07/06/2021	Regulation Change
3.1.6.5	09/06/2021	Template Change
3.1.6.6	11/06/2021	Template Change
3.1.6.7	15/06/2021	Template Change
3.1.7.7	17/06/2021	Regulation Change
3.1.8.7	21/06/2021	Regulation Change
3.1.8.8	05/07/2021	Template Change

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Chemwatch: 5396-80 Page 9 of 9 Issue Date: 03/09/2020 Version No: 3.1.8.8 Print Date: 12/07/2021

Ardex WR Prime

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.