

Ardex (Ardex Australia)

Chemwatch: 85-5520 Version No: 8.1.1.1 Safety Data Sheet according to WHS and ADG requirements

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	Ardex RA 84 Part B
Synonyms	Not Available
Other means of identification	Not Available
Other means of identification	

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Hardener component.
--------------------------	---------------------

## Details of the supplier of the safety data sheet

Registered company name	Ardex (Ardex Australia)
Address	20 Powers Road Seven Hills NSW 2147 Australia
Telephone	1800 224 070
Fax	1300 780 102
Website	Not Available
Email	Not Available

#### Emergency telephone number

<u> </u>	
Association / Organisation	Ardex (Ardex Australia)
Emergency telephone numbers	1800 224 070 (Mon-Fri, 9am-5pm)
Other emergency telephone numbers	Not Available

## **SECTION 2 HAZARDS IDENTIFICATION**

## Classification of the substance or mixture

# HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

## CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	1 📕		
Toxicity	0	1	0 = Minimum
Body Contact	3		1 = Low 2 = Moderate
Reactivity	1	1	3 = High
Chronic	2	i	4 = Extreme

Poisons Schedule	S5	
Classification <sup>[1]</sup>	Eye Irritation Category 2A, Skin Sensitizer Category 1, Specific target organ toxicity - repeated exposure Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

# Label elements

Hazard pictogram(s)	
SIGNAL WORD	WARNING

Chemwatch Hazard Alert Code: 3

Issue Date: 07/03/2020

Print Date: 14/07/2020 S.GHS.AUS.EN

Continued...

#### Hazard statement(s)

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
Precautionary statement(s) Pre	vention
Precautionary statement(s) Pre	vention Do not breathe mist/vapours/spray.

## Precautionary statement(s) Response

P272

P321	Specific treatment (see advice on this label).
P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contaminated work clothing should not be allowed out of the workplace.

#### Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
94-36-0	10-25	dibenzoyl peroxide
107-21-1	5-10	ethylene glycol
Not Available	>60	Ingredients determined not to be hazardous

# **SECTION 4 FIRST AID MEASURES**

	If this product comes in contact with the eyes:
Eye Contact	<ul> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> </ul>
	<ul> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	If skin contact occurs:  If skin contact occurs: Immediately remove all contaminated clothing, including footwear.
Skin Contact	<ul> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> </ul>
Inhalation	<ul> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>
	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiratio</li> <li>Observe the patient carefully.</li> </ul>
Ingestion	<ul> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# SECTION 5 FIREFIGHTING MEASURES

## Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

# Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
vice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>Combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>metal oxides</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit corrosive fumes.</li> </ul>
HAZCHEM	Not Applicable

# SECTION 6 ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid contact with skin and eyes.</li> <li>Wear impervious gloves and safety goggles.</li> <li>Trowel up/scrape up.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# SECTION 7 HANDLING AND STORAGE

## Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>

#### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	<ul> <li>Avoid storage with reducing agents.</li> <li>Avoid cross contamination between the two liquid parts of product (kit).</li> <li>If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur.</li> <li>This excess heat may generate toxic vapour</li> <li>Avoid strong acids, bases.</li> </ul>

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Control parameters**

# OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	ethylene glycol	Ethylene glycol (particulate)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	ethylene glycol	Ethylene glycol (vapour)	20 ppm / 52 mg/m3	104 mg/m3 / 40 ppm	Not Available	Not Available

## EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
dibenzoyl peroxide	Benzoyl peroxide	15 mg/m3	1,200 mg/m3	7,000 mg/m3
ethylene glycol	Ethylene glycol	30 ppm	150 ppm	900 ppm
Ingredient	Original IDLH		Revised IDLH	
dibenzoyl peroxide	1,500 mg/m3		Not Available	
ethylene glycol	Not Available		Not Available	

#### Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	<ul> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>NOTE:</li> <li>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul>
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> </ul>

## Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

Ardex RA 84 Part B

Material	СРІ
NATURAL RUBBER	A
NATURAL+NEOPRENE	A
NEOPRENE	А
NEOPRENE/NATURAL	А
NITRILE	A
NITRILE+PVC	А
PE/EVAL/PE	A
PVC	А
TEFLON	A
PVA	В

## \* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## **Respiratory protection**

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Appearance	Gray paste with characteristic odour; does not mix with wa	ater.	
Physical state	Non Slump Paste	Relative density (Water = 1)	1.45
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	50
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# SECTION 10 STABILITY AND REACTIVITY

See section 7
<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
See section 7
See section 7
See section 7
See section 5

# SECTION 11 TOXICOLOGICAL INFORMATION

# Information on toxicological effects

Inhaled			
ingestion       corroborating animal or human evidence.         corroborating animal or human evidence.       Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.         Open cuts, abraded or irritated skin should not be exposed to this material       Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the prior to the use of the material and ensure that any external damage is suitably protected.         There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.         Eve       Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Prolonged contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).         Skin contact       Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure to this material may result in reduced fertility. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).         Ardex RA 84 Par	Inhaled	co-ordination, and vertigo.	s may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of
Skin Contact       Open cuts, abraded or irritated skin should not be exposed to this material         Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the prior to the use of the material and ensure that any external damage is suitably protected.         There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.         Eye       Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Prolonged contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).         Skin contact       Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure to this material may result in reduced fertility. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).         Ardex RA 84 Part B       TOXICITY       IRRITATION	Ingestion	,	classification systems as "harmful by ingestion". This is because of the lack of
Eye       contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).         Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposur There is some evidence from animal testing that exposure to this material may result in reduced fertility. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).         Ardex RA 84 Part B       TOXICITY       IRRITATION	Skin Contact	Open cuts, abraded or irritated skin should not be exposed to th Entry into the blood-stream, through, for example, cuts, abrasion prior to the use of the material and ensure that any external dan There is some evidence to suggest that the material may cause	is material ns or lesions, may produce systemic injury with harmful effects. Examine the skin nage is suitably protected. mild but significant inflammation of the skin either following direct contact or after
Chronic       There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposur There is some evidence from animal testing that exposure to this material may result in reduced fertility. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).         Ardex RA 84 Part B       TOXICITY	Eye		
Ardex RA 84 Part B	Chronic	There has been some concern that this material can cause can Substance accumulation, in the human body, may occur and ma There is some evidence from animal testing that exposure to thi There is some evidence from animal testing that exposure to thi	cer or mutations but there is not enough data to make an assessment. ay cause some concern following repeated or long-term occupational exposure. is material may result in reduced fertility. is material may result in toxic effects to the unborn baby.
Oral (None) LD50: 10000 mg/kg* <sup>[2]</sup> Not Available	Ardov PA 84 Part B	TOXICITY	IRRITATION
		Oral (None) LD50: 10000 mg/kg* <sup>[2]</sup>	Not Available
TOXICITY IRRITATION		ΤΟΧΙΟΙΤΥ	IRRITATION
dibenzoyl peroxide     dermal (mammal) LD50: >1000 mg/kg <sup>[2]</sup> Eye (rabbit): 500 mg/24h - mild	dibenzoyl peroxide	dermal (mammal) LD50: >1000 mg/kg <sup>[2]</sup>	Eye (rabbit): 500 mg/24h - mild
Oral (rat) LD50: 6400 mg/kg <sup>[2]</sup> Skin effects (MAK): very weak		Oral (rat) LD50: 6400 mg/kg <sup>[2]</sup>	Skin effects (MAK): very weak
TOXICITY IRRITATION		ΤΟΧΙΟΙΤΥ	IRRITATION
Dermal (rabbit) LD50: 9530 mg/kg <sup>[2]</sup> Eye (rabbit): 100 mg/1h - mild		Dermal (rabbit) LD50: 9530 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg/1h - mild
ethylene glycol         Inhalation (rat) LC50: 100.2 mg/l/8hr <sup>[2]</sup> Eye (rabbit): 12 mg/m3/3D	ethylene glycol	Inhalation (rat) LC50: 100.2 mg/l/8hr <sup>[2]</sup>	Eye (rabbit): 12 mg/m3/3D
Oral (rat) LD50: =3.58-12.7 mg/kg <sup>[2]</sup> Eye (rabbit): 1440mg/6h-moderate		Oral (rat) LD50: =3.58-12.7 mg/kg <sup>[2]</sup>	Eye (rabbit): 1440mg/6h-moderate

Continued...

		Eye (rabbit): 500	mg/24h - mild
		Eye: no adverse	effect observed (not irritating) <sup>[1]</sup>
		Skin (rabbit): 55	5 mg(open)-mild
		Skin: no adverse	effect observed (not irritating) <sup>[1]</sup>
Legend:	1. Value obtained from Europe ECHA Registered Sub- specified data extracted from RTECS - Register of Tox		ined from manufacturer's SDS. Unless otherwise
DIBENZOYL PEROXIDE	The following information refers to contact allergens as Contact allergies quickly manifest themselves as contact eczema involves a cell-mediated (T lymphocytes) imm involve antibody-mediated immune reactions. The sign distribution of the substance and the opportunities for of The material may be irritating to the eye, with prolonged conjunctivitis. The material may cause skin irritation after prolonged vesicles, scaling and thickening of the skin. Benzoyl peroxide may cause double vision, breathing activity. It did not produce blood or biochemical advers decreased weights of testes and the newborn. The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limit	act eczema, more rarely as urticaria c nune reaction of the delayed type. Oth ifficance of the contact allergen is not contact with it are equally important. ad contact causing inflammation. Rep or repeated exposure and may produ problems, excess saliva and tear forr a effects, gene mutation or evidence	r Quincke's oedema. The pathogenesis of contact er allergic skin reactions, e.g. contact urticaria, simply determined by its sensitisation potential: the eated or prolonged exposure to irritants may produce ce on contact skin redness, swelling, the production o nation, redness of the skin and changes in motor
ETHYLENE GLYCOL	[Estimated Lethal Dose (human) 100 ml; RTECS quote For ethylene glycol: Ethylene glycol is quickly and extensively absorbed the through the ginguist characteristics through glyin is generated	roughout the gastrointestinal tract. Lir	nited information suggests that it is also absorbed
	metabolized by alcohol dehydrogenase to form glycoa		
Acute Toxicity			listributed throughout the body. In humans, it is initially glycolic acid and glyoxal.
	metabolized by alcohol dehydrogenase to form glycoa	Idehyde, which is rapidly converted to	glycolic acid and glyoxal.
Acute Toxicity Skin Irritation/Corrosion	metabolized by alcohol dehydrogenase to form glycoa	Idehyde, which is rapidly converted to Carcinogenicity	glycolic acid and glyoxal.
Acute Toxicity	metabolized by alcohol dehydrogenase to form glycoa	ldehyde, which is rapidly converted to Carcinogenicity Reproductivity	glycolic acid and glyoxal.

# **SECTION 12 ECOLOGICAL INFORMATION**

# Toxicity

Ardex RA 84 Part B	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCI
	LC50	96	Fish	0.06mg/L	2
dibenzoyl peroxide	EC50	48	Crustacea	0.11mg/L	2
	EC50	72	Algae or other aquatic plants	0.042mg/L	2
	NOEC	72	Algae or other aquatic plants	0.02mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCI
	LC50	96	Fish	>72-860mg/L	2
ethylene glycol	EC50	48	Crustacea	>100mg/L	2
	EC50	96	Algae or other aquatic plants	3-536mg/L	2
	NOEC	552	Crustacea	>=1-mg/L	2
Legend:	V3.12 (QSAR) -	Aquatic Toxicity Data (Estimated) 4. L	HA Registered Substances - Ecotoxicological Inform. JS EPA, Ecotox database - Aquatic Toxicity Data 5. I ( (Japan) - Bioconcentration Data 8. Vendor Data	, , ,	

# **DO NOT** discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
dibenzoyl peroxide	LOW (Half-life = 14 days)	LOW (Half-life = 21.25 days)	
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)	

# **Bioaccumulative potential**

Ingredient

Bioaccumulation

ethylene glycol

## Ardex RA 84 Part B

dibenzoyl peroxide	LOW (LogKOW = 3.46)
ethylene glycol	LOW (BCF = 200)
Mobility in soil	
Ingredient	Mobility
dibenzoyl peroxide	LOW (KOC = 771)

## SECTION 13 DISPOSAL CONSIDERATIONS

HIGH (KOC = 1)

## Waste treatment methods

Product / Packaging disposal	<ul> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> <li>Otherwise: <ul> <li>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>DO NOT allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Authority for disposal.</li> <li>Bury or incinerate residue at an approved site.</li> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul> </li> </ul>
------------------------------	--

## **SECTION 14 TRANSPORT INFORMATION**

#### Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

## Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## SECTION 15 REGULATORY INFORMATION

## Safety, health and environmental regulations / legislation specific for the substance or mixture

#### DIBENZOYL PEROXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2  $\,$ 

#### ETHYLENE GLYCOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Inventory of Chemical Substances (AICS) Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4  $\,$ 

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 6

Chemical Footprint Project - Chemicals of High Concern List

#### **National Inventory Status**

National Inventory	Status	
Australia - AICS	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (dibenzoyl peroxide; ethylene glycol)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	

USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## **SECTION 16 OTHER INFORMATION**

Revision Date	07/03/2020
Initial Date	19/09/2017

#### **SDS Version Summary**

Version	Issue Date	Sections Updated
7.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
8.1.1.1	07/03/2020	Classification change due to full database hazard calculation/update.

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure  $\mathsf{Limit}_\circ$ IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

