

# Ardex E90 Ardex (Ardex Australia)

Chemwatch: 5457-33 Version No: 2.1.1.1 Safety Data Sheet according to WHS and ADG requirements

# Chemwatch Hazard Alert Code: 2

Issue Date: 08/03/2021 Print Date: 08/03/2021 S.GHS.AUS.EN

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	Ardex E90
Chemical Name	Not Applicable
Synonyms	Ardion 90; water based bonding agent
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Balance i la sella da ser	Wa
Relevant identified uses	

Water reducible styrene/butylacrylic. Use according to manufacturer's directions.

## Details of the supplier of the safety data sheet

Registered company name	Ardex (Ardex Australia)	
Address	20 Powers Road Seven Hills NSW 2147 Australia	
Telephone	1800 224 070	
Fax	1300 780 102	
Website	Not Available	
Email	Not Available	

#### Emergency telephone number

Association / Organisation	Ardex (Ardex Australia)
Emergency telephone numbers	1800 224 070 (Mon-Fri, 9am-5pm)
Other emergency telephone numbers	Not Available

## **SECTION 2 Hazards identification**

## Classification of the substance or mixture

## HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Ha	zard Ratings		
	Min	Max	
Flammability	0		
Toxicity	1		0 = Minimum
Body Contact	0	1	1 = Low
Reactivity	1	1	2 = Moderate
Chronic	2		3 = High 4 = Extreme

Poisons Schedule	Not Applicable
Classification <sup>[1]</sup>	Skin Sensitizer Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

May cause an allergic skin reaction.

## Precautionary statement(s) Prevention

H317

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/	
P261	Avoid breathing mist/vapours/spray.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

#### Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	

## Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

## **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
9004-34-6	1-10	cellulose
2634-33-5	<0.1	1.2-benzisothiazoline-3-one
2682-20-4	<0.1	2-methyl-4-isothiazolin-3-one
55965-84-9	<0.1	isothiazolinones, mixed
Not Available	balance	Ingredients determined not to be hazardous

#### **SECTION 4 First aid measures**

#### Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	If skin contact occurs: <ul> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

Indication of any immediate medical attention and special treatment needed Treat symptomatically.

Issue Date: 08/03/2021

Print Date: 08/03/2021

## Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Advice for firefighters			
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>		
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>Decomposes on heating and produces: carbon dioxide (CO2) hydrogen bromide other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>		
HAZCHEM	Not Applicable		

#### **SECTION 6 Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul>
Major Spills	Moderate hazard. <ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

Precautions for safe handling Safe handling	<ul> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> </ul>
Other information	<ul> <li>Prevent concentration in hollows and sumps.</li> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> </ul>

#### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Avoid reaction with oxidising agents

## **SECTION 8 Exposure controls / personal protection**

#### Control parameters

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	cellulose	Cellulose (paper fibre)	10 mg/m3	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Emergency Limits						
Ingredient	TEEL-1			TEEL-2		TEEL-3

Ingredient	TEEL-1	TEEL-2		TEEL-3
Ardex E90	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
cellulose	Not Available		Not Available	
1,2-benzisothiazoline-3-one	Not Available		Not Available	
2-methyl-4-isothiazolin-3-one	Not Available		Not Available	
isothiazolinones, mixed	Not Available		Not Available	
Occupational Exposure Banding				
Ingredient	Occupational Exposure Band Rating		Occupational Expos	ure Band Limit

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
1,2-benzisothiazoline-3-one	E	≤ 0.01 mg/m³	
2-methyl-4-isothiazolin-3-one	D	> 0.01 to ≤ 0.1 mg/m³	
isothiazolinones, mixed	E	≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a		

adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

## Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	<ul> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>NOTE:</li> <li>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</li> <li>Personal hygiene is a key element of effective hand care.</li> </ul>
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> </ul>

#### Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

900		00.00
Ardex	E90	

Material	CPI
BUTYL	А
NEOPRENE	A
VITON	А
NATURAL RUBBER	С
PVA	С

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such

#### Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance White liquid with a weak characteristic odour; mixes with water.

Physical state	Liquid	Relative density (Water = 1)	1.04
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8-9	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100 approx.	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	42-44
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## **SECTION 11 Toxicological information**

## Information on toxicological effects

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. Cellulose, given via the windpipe, caused fibrosis in the alveoli and airways, with injuries of the lung cells. Some health effects associated with wood, cotton, flax, jute and hemp particles or fibres are not attributable to cellulose content but to other substances and/or impurities.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby. Inhalation studies using animals have shown that cellulose fibres can cause lung scarring, and humans exposed to cellulose at work are more likely to develop asthma and obstructive lung disease. The substance may also induce the production of free radicals in human white blood cells. < Studies indicate that diets containing large amounts of non-absorbable polysaccharides, such as cellulose, might decrease absorption of calcium,

magnesium, zinc and phosphorus. This material contains a substantial amount of polymer considered to be of low concern. These are classified under having MWs of between 1000 to 10000 with less than 25% of molecules with MWs under 1000 and less than 10% under 500; or having a molecular weight average of over 10000.

Chronic poisoning from ionic bromides has historically resulted from medical use of bromides but not from exposure in the environment or workplace. In the absence of other signs of poisoning, there may be depression, hallucinations and schizophrenia-like psychosis. Bromides may also cause sedation, irritability, agitation, delirium, memory loss, confusion, disorientation, forgetfulness, inability to speak, difficulty speaking, weakness, fatigue, a spinning sensation, stupor, coma, decreased appetite, nausea, vomiting, an acne-like rash on the face (bronchoderma), legs and trunk, swelling of the bronchi and a profuse discharge from the nostrils. There may also be inco-ordination and very brisk reflexes.

4 . Lux 500	ΤΟΧΙΟΙΤΥ	IRRITATION	
Ardex E90	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Not Available	
cellulose	Inhalation(Rat) LC50; >5.8 mg/L4 <sup>[2]</sup>		
	Oral(Rat) LD50; >5000 mg/kg <sup>[2]</sup>		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
1,2-benzisothiazoline-3-one	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>	
	Oral(Rat) LD50; 454 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	dermal (rat) LD50: 242 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>	
2-methyl-4-isothiazolin-3-one	Inhalation(Rat) LC50; 0.1 mg/l4 <sup>[1]</sup>	Skin: adverse effect observed (corrosive) <sup>[1]</sup>	
	Oral(Rat) LD50; 120 mg/kg <sup>[1]</sup>		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	dermal (rat) LD50: >1008 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>	
isothiazolinones, mixed	Inhalation(Rat) LC50; 0.171 mg/l4 <sup>[1]</sup>	Skin: adverse effect observed (corrosive) <sup>[1]</sup>	
	Oral(Rat) LD50; 66 mg/kg <sup>[1]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>	
l ogondi	end: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

1,2-BENZISOTHIAZOLINE-3-ONE	Acute toxicity data show that 1,2-benzisothiazoline-3-one (BIT) is moderately toxic by the oral and dermal routes but that this chemical is a severe eye irritant. Irritation to the skin from acute data show only mild skin irritation , but repeated dermal application indicated a more significant skin irritation response. The neurotoxicity observed in the rat acute oral toxicity study (piloerection and upward curvature of the spine at 300 mg/kg and above; decreased activity, prostration, decreased abdominal muscle tone, reduced righting reflex, and decreased rate and depth of breathing at 900 mg/kg) and the acute dermal toxicity study (upward curvature of the spine was observed in increased incidence, but this was absent after day 5 post-dose at a dose of 2000 mg/kg) were felt to be at exposures in excess of those expected from the use pattern of this pesticide and that such effects would not be observed at estimated exposure doese. <b>Subchronic oral toxicity</b> studies showed systemic effects after repeated oral administration including decreased body weight, increased incidence of forestomach hyperplasia, and non-glandular stomach lesions in rats. In dogs, the effects occurred at lower doses than in rats, and included alterations in blood chemistry (decreased plasma albumin, total protein, and alanine aminotransferase) and increased food consumption, and clinical toxicity signs (audible breathing, haircoat staining of the anogenital region, dry brown material around the nasal area) as well as increased mortality. Developmental effects consisted of increases in skeletal abnormalities (extra sites of ossification of skull bones, unossified sternebrae) but not external or visceral abnormalities.
2-METHYL- 4-ISOTHIAZOLIN-3-ONE	Based on laboratory and animal testing, exposure to the material may result in irreversible effects and mutations in humans. In light of potential adverse effects, and to ensure a harmonised risk assessment and management, the EU regulatory framework for biocides has been established with the objective of ensuring a high level of protection of human and animal health and the environment. To this aim, it is required that risk assessment of the biocidal products is carried out before they can be placed on the market. A central element in the risk assessment of the biocidal products are the utilization instructions that defines the dosage, application method and amount of applications and thus the exposure of humans and the environment to the biocidal substance. Humans may be exposed to biocidal products in different ways in both occupational and domestic settings. Many biocidal products are intended for industrial sectors or professional uses only, whereas other biocidal products are commonly available for private use by non-professional users. Formaldehyde generators (releasers) are often used as preservatives. The maximum authorised concentration of free formaldehyde is 0.2% and must be labelled with the warning sign "contains formaldehyde" where the concentration exceeds 0.05%. The use of formaldehyde-releasing preservatives ensures that the level of free formaldehyde in the products is always low but sufficient to inhibit microbial growth - it disrupts metabolism to cause death of the organism. However there is a concern that formaldehyde generators can produce amines capable of causing cancers (nitrosamines) when used in formulations containing amines. <b>NOTE:</b> Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA. Considered to be a minor sensitiser in Kathon CG (1) (1). Bruze etal - Contact Dermatitis 20: 219-39, 1989
CELLULOSE & 2-METHYL- 4-ISOTHIAZOLIN-3-ONE & ISOTHIAZOLINONES, MIXED	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack

Page 7 of 9 Ardex E90

	of minimal lymphocytic inflammation, without eosinophilia.		
1,2-BENZISOTHIAZOLINE-3-ONE & 2-METHYL- 4-ISOTHIAZOLIN-3-ONE & ISOTHIAZOLINONES, MIXED	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important.		
2-METHYL- 4-ISOTHIAZOLIN-3-ONE & ISOTHIAZOLINONES, MIXED	No significant acute toxicological data identified in literature search. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
			t available or does not fill the criteria for classification to make classification

## **SECTION 12 Ecological information**

## Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
Ardex E90	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
cellulose	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48	Crustacea	0.001mg/L	4
1,2-benzisothiazoline-3-one	LC50	96	Fish	<=0.002mg/L	4
	EC50(ECx)	48	Crustacea	0.001mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	<0.001mg/L	4
-methyl-4-isothiazolin-3-one	EC50	48	Crustacea	<0.001mg/L	4
	EC50(ECx)	48	Crustacea	<0.001mg/L	4
	EC50	96	Algae or other aquatic plants	0.063mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	NOEC(ECx)	504	Crustacea	0.004mg/l	2
isothiazolinones, mixed	LC50	96	Fish	0.129mg/l	2
	EC50	48	Crustacea	0.007mg/l	2
Legend:	V3.12 (QSAR)	- Aquatic Toxicity Data (Estimated) 4.	HA Registered Substances - Ecotoxicological Informa US EPA, Ecotox database - Aquatic Toxicity Data 5. E 1 (Japan) - Bioconcentration Data 8. Vendor Data		

## DO NOT discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
cellulose	LOW	LOW
2-methyl-4-isothiazolin-3-one	HIGH	HIGH

## **Bioaccumulative potential**

Ingredient	Bioaccumulation
cellulose	LOW (LogKOW = -5.1249)
2-methyl-4-isothiazolin-3-one	LOW (LogKOW = -0.8767)

## Mobility in soil

Ingredient	Mobility
cellulose	LOW (KOC = 10)
2-methyl-4-isothiazolin-3-one	LOW (KOC = 27.88)

## **SECTION 13 Disposal considerations**

Product / Packaging disposal	<ul> <li>DO NOT allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>Decontaminate empty containers.</li> </ul>
------------------------------	--

## **SECTION 14 Transport information**

#### Labels Required

Marine Pollutant	NO	
HAZCHEM	Not Applicable	

#### Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

## Transport in bulk according to Annex II of MARPOL and the IBC code

## Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
cellulose	Not Available
1,2-benzisothiazoline-3-one	Not Available
2-methyl-4-isothiazolin-3-one	Not Available
isothiazolinones, mixed	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
cellulose	Not Available
1,2-benzisothiazoline-3-one	Not Available
2-methyl-4-isothiazolin-3-one	Not Available
isothiazolinones, mixed	Not Available

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for

Manufactured Nanomaterials (MNMS)

Australian Inventory of Industrial Chemicals (AIIC)

Australian Inventory of Industrial Chemicals (AIIC)

#### **SECTION 15 Regulatory information**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

#### cellulose is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

#### 1,2-benzisothiazoline-3-one is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

## 2-methyl-4-isothiazolin-3-one is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 6

#### isothiazolinones, mixed is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

#### **National Inventory Status**

National InventoryStatusAustralia - AIIC / Australia<br/>Non-Industrial UseNo (isothiazolinones, mixed)Canada - DSLYesCanada - NDSLNo (1,2-benzisothiazoline-3-one; 2-methyl-4-isothiazolin-3-one; isothiazolinones, mixed)China - IECSCYesEurope - EINEC / ELINCS / NLPNo (isothiazolinones, mixed)No (isothiazolinones, mixed)No (isothiazolinones, mixed)

Ardex	E90

National Inventory	Status	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	No (isothiazolinones, mixed)	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (isothiazolinones, mixed)	
Vietnam - NCI	Yes	
Russia - ARIPS	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

#### **SECTION 16 Other information**

Revision Date	08/03/2021
Initial Date	08/03/2021

#### **SDS Version Summary**

Version	Issue Date	Sections Updated
2.1.1.1	08/03/2021	Ingredients

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.