



## ARDEX Building Product Information Sheet: Industrial Coatings

|   |   |
|---|---|
| Product name:   | Industrial Coatings   |
| Product line (the product line from which the product is customised)      | Industrial Coatings   |
| Product description and its intended use (measurements, materials, usage) | Industrial coatings products serve a variety of purposes. They can protect surfaces e.g., from corrosion, abrasion and weathering. They can also be used for decorative reasons, used to enhance the appearance of surfaces e.g., polyurethane for a glossy finish, as well as to improve performance of surfaces such as through anti-slip coatings or increased durability.   |
| Product identifier (if applicable):                                       | <p>Specialist polyurethane flooring resin ARDEX R 70 P and screed R 90 P (indent only)</p> <p>18454 - ARDEX R 90 P filler 23kg<br/> 18457 - ARDEX R 70/90 P, Part A, 2.67kg<br/> 16197 – ARDEX R 70/90 P, Part B, 2.86kg</p> <p>Highly conductive water based epoxy (indent only)</p> <p>38113 - ARDEX R 7 E, Part A, 20.5kg<br/> 38114 – ARDEX R 7 E, Part B, 4.5kg</p> <p>Water based aliphatic polyurethane membrane (2 coats)</p> <p>38112 - ARDEX WPM 170 Grey 20kg</p> <p>Two component epoxy resin – ARDEX R 4 E and R 5 E</p> <p>38115 - ARDEX R 4 E, Part A, 4.667kg<br/> 38116 – ARDEX R 4 E, Part B, 2.333kg<br/> 38109 – ARDEX R 5 E Part A, 13.88kg<br/> 38110 – ARDEX R 5 E Part B, 6.12kg</p> <p>Conductive epoxy coating</p> <p>ARDEX R 27 E</p> <p>Self-levelling epoxy with antistatic properties (indent only)</p> <p>ARDEX R 77 E</p> <p>Solvent free, Self-levelling polyurethane resin</p> <p>44307 ARDEX R 76 PU RAL TBC 15.7kg (colours made to order)</p> <p>ARDEX R 20 PU coloured polyurethane roll coat system for internal and external use (2 coats)</p> <p>44306 ARDEX R 20 PU Part A RAL TBC 8.1 kg (colours made to order)<br/> 34267 ARDEX R 20 PU Part B 2.13kg</p> <p>A transparent, anti-scratch aliphatic polyurethane coating</p> <p>38103 ARDEX R 21 PU Part A 7.5Kg<br/> 38104 ARDEX R 21 PU Part B 2.5 Kg</p> |



|  |   |
|--|---|
|  | <p>A solvent-free polyurethane resin for creating coloured, elastic flooring indent)</p> <p>45474 ARDEX R 74 RAL TBC Part A 16.916kg (colours made to order)</p> <p>45025 ARDEX R 74 Elastico Part B 3.084kg</p> <p>ARDEX R 50 ES multipurpose epoxy resin</p> <p>38129 – ARDEX R 50 ES Part B, 4.813kg</p>   |
| Place of manufacture:  | Overseas  |
| Legal and trading name of the manufacturer(s):                                 | Seire – Spain an ARDEX Group Company  |
| Legal and trading name of the importer   | ARDEX New Zealand Ltd   |
| Address for service:   | 15 Alfred Street, Onehunga<br>Auckland New Zealand 1061   |
| Website:   | ardex.co.nz   |
| Email address  | info@ardexnz.com  |
| Phone No   | 0800 227 339  |
| NZBN   | 9429037589653   |
| Relevant Building Code clauses:  | B2 DURABILITY Performance B2.3.1 (C)<br>D1 Slip resistance (Contributes)<br>F2 HAZARDOUS BUILDING MATERIALS: Performance  |
| Statement on how the building product is expected to contribute to compliance: | <p>ARDEX industrial coatings will provide suitable floor finishes for direct foot traffic, where slip resistance is required the addition of aggregates in the coating will assist in achieving the desired finished level.</p> <p>ARDEX takes responsibility for the quality of its products. The applications and recommendations given are based on extensive testing and quality control.</p> <p>ARDEX industrial coatings will not have a service life of less than 5 years and minimum warranty offered by ARDEX is 10 years.</p> |
| Limitations on the use of the building product:                                | Please refer to the relevant datasheet for more information   |
| Design requirements that would support the use of the building product:        | Applications that require a coating finish, exceptional hygiene control and decorative look. ARDEX can tint the products to most RAL colours.   |
| Installation requirements:   | Please refer to the relevant datasheet for more information   |
| Maintenance requirements:  | <p>Perimeter sealants shall be maintained as per the respective manufacturers requirements.</p> <p>Surface cleaning shall be undertaken in accordance with the maintenance plan provided by the installer.</p>  |



|  |  |
|--|--|
| Is the building product/building product line subject to warning or ban under section 26?: | No   |
|  | <b>ARDEX BPIS Industrial Coatings v2 4.07.24</b> |