

## **ARDEX Building Product Information Sheet: Shelterseal Systems**

Product name:	ARDEX Shelterseal systems
Product line (the product line from which the product is customised)	Damp-proofing membrane systems
Product description and its intended use	Products forming the ARDEX WPM 3000X and 5000HD systems covered by this BPIRS are:
(measurements, materials, usage)	Shelterseal Membranes
	Shelterseal 3000X - a membrane manufactured from a bituminous asphalt compound modified with SBS (styrene-butadiene-styrene) rubber and high tack resins. The self-adhesive inner face is protected by a release paper with the outer surface protected by high-density polyethylene film. The membrane is 1.5 mm thick, and supplied in rolls 1 m wide by 20 m long.
	Shelterseal 5000HD - a membrane manufactured from a bituminous asphalt compound modified with SBS rubber and high tack resins. The self-adhesive inner face is protected by a release paper with the outer surface protected by a layer of polypropylene mesh. Shelterseal 5000HD is designed for use where a more robust system is required. The membrane is 1.5 mm thick, and supplied in rolls 1 m wide by 20 m long. The roll weight is approximately 30 kg.
	ARDEX DRS 10GC - a dimpled HDPE sheet with a geotextile layer that provides drainage and protection against back filling. It is supplied in rolls 10 mm thick by 2 m wide and 20 m long.
	Primers
	WPM 240 - a solvent-based, bitumen-modified primer. It is supplied in 5 or 20 L containers and is coloured black.
	WPM 247 Primer - a water-based, bitumen emulsion primer. It is supplied in 5 or 20 L containers and is coloured black.
	WA 98 Contact Adhesive/Primer - a contact adhesive that can be used as a primer in difficult drying conditions. It can be spray-applied. It is supplied in 4 or 20 L containers and is coloured red or clear.
	Bituminous Sealant - a black bituminous sealant supplied in 300 ml cartridges.
Product identifier (if applicable):	10543 – WPM 3000 X 10544 – WPM 5000 HD 32142 – DRS 10 GC
	11171 – WPM 247



	13052 - WARR adhesive 201 (red)
	13052 – WA98 adhesive 20L (red) 24188 – WA98 adhesive 20L (clear)
	10870 – WA98 adhesive 4L
	30146 – WPM1955 Hydrostop SEA 20mm x 10mm x 8m
Place of	Overseas
manufacture:	
Legal and trading	ISOLTEMA Group
name of the	
manufacturer(s):	
Legal and trading	ARDEX New Zealand Ltd
name of the	
importer	
Address for	15 Alfred Street, Onehunga
service:	Auckland New Zealand 1061
Website:	ardex.co.nz
Email address	info@ardexnz.com
Phone No	0800 227 339
NZBN	9429037589653
Relevant Building	Clause B2 DURABILITY: Performance B2.3.1 (A) not less than 50 years
Code clauses:	Clause E2 EXTERNAL MOISTURE: Performance E2.3.3
	Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1
Statement on	ARDEX SHELTERSEAL systems have been BRANZ appraised as damp-proof
how the building	membranes for use under floor slabs complying with NZS 3604 and as damp-
product is	proof membrane behind concrete masonry basement walls and under floor
expected to	slabs complying with NZS 4229. And as damp-proof membranes on buildings
contribute to	subject to specific design.
compliance:	,
Limitations on the	Refer technical datasheet
use of the	
building product:	Do not use in hydrostatic situations.
	Drainage behind wall is required.
Design	
requirements	for basement retaining walls and floors. They are applied under floor slabs
that would	and foundations, and to the exterior face of basement retaining walls to
support the use	prevent water vapour penetrating to the interior face in spaces where
of the building	moisture may cause damage
product:	
Installation	Products must be installed by ARDEX NZ approved applicators and in
requirements:	according with the relevant technical datasheets and BRANZ appraisal
	instructions.



Maintenance requirements:	No maintenance of the membrane is normally required provided significant substrate movement does not occur.
Is the building product/building product line subject to warning or ban under section 26?:	No
	ARDEX BPIS Shelterseal Systems v1 9/10/23