



ARDEX Building Product Information Sheet: Silicones & CA 20 P PLUS

Product name:	ARDEX CA 20 P PLUS and ARDEX Silicones (SE + ST)
Product line (the product line from which the product is customised)	Tiling (Silicones) and General Construction adhesive (CA 20 P PLUS)
Product description and its intended use (measurements, materials, usage)	ARDEX CA 20 P PLUS – A multipurpose construction sealant and adhesive ARDEX ST – a neutral cure silicone sealant ARDEX SE – an acetic cure silicone sealant
Product identifier (if applicable):	<p>44435 – CA 20 P PLUS Black 310ml 44434 – CA 20 P PLUS Grey 310ml 44486 – CA 20 P PLUS White 310ml</p> <p>24369 – ARDEX SE Slate Grey 310ml 24365 – ARDEX SE Magellan Grey 310ml 24372 – ARDEX SE Ultra White 310ml 24368 – ARDEX SE Misty Grey 310ml 24363 – ARDEX SE Charred Ash 310ml 24366 – ARDEX SE Midnight 310ml 24382 – ARDEX SE Olive 310ml 24383 – ARDEX SE Macchiato 310ml 24370 – ARDEX SE Todd River Sand 310ml 24367 – ARDEX SE Mudberry 310ml 24364 – ARDEX SE Havana 310ml 24362 – ARDEX SE Buff 310ml 24361 – ARDEX SE Alabaster 310ml 24371 – ARDEX SE Travertine 310ml</p> <p>10180 – ARDEX ST Ultrawhite 310ml 10178 – ARDEX ST Slate Grey 310ml 10179 – ARDEX ST Travertine 310ml 10176 – ARDEX ST Misty Grey 310ml 10174 – ARDEX ST Charred Ash 310ml 10173 – ARDEX ST Alabaster 310ml</p>
Place of manufacture:	Overseas
Legal and trading name of the manufacturer(s):	ARDEX AUSTRALIA
Legal and trading name of the importer	ARDEX New Zealand Ltd



Address for service:	15 Alfred Street, Onehunga Auckland New Zealand 1061
Website:	ardex.co.nz
Email address	info@ardexnz.com
Phone No	0800 227 339
NZBN	9429037589653
Relevant Building Code clauses:	B2 DURABILITY Performance B2.3.1 & B2.3.2 E2 EXTERNAL MOISTURE (Contributes) Performance E2.3.2, E2.3.3 E3 INTERNAL MOISTURE (Contributes) Performance E3.3.3, E3.3.4, E3.3.5, E3.3.6 F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1
Statement on how the building product is expected to contribute to compliance:	B2 – Products have been tested and comply with the requirements of ISO 11600 Type F 25LM Performance E2.3.2. When used as part of the tiling system, ARDEX Sealants will contribute to meeting this requirement Performance E3.3.3, E3.3.4, E3.3.5 and E3.3.6. When used as part of the substrate lining or finishing system, ARDEX sealants will contribute to meeting these requirements. F2 – CA 20 P PLUS and SE/ST Silicones all have VOC certificates found at ardex.co.nz
Limitations on the use of the building product:	Please refer to the datasheet at ardex.co.nz ARDEX SE should not be used with natural stone tiles.
Design requirements that would support the use of the building product:	ARDEX CA 20 P is a multiuse construction adhesive and Sealant typically used for sealing membranes into chases and small tile repairs. ARDEX SE and ST are used as part of the ARDEX Tiling systems for finishing movement joints and sealing perimeter of the Tiling. ARDEX ST is neutral cure and ARDEX SE is an acetic cure silicone.
Installation requirements:	Please refer to the datasheet at ardex.co.nz
Maintenance requirements:	General Cleaning and maintenance should be carried out as part of normal household duties.
Is the building product/building product line subject to warning or ban	No



under section 26?:	
	ARDEX BPIRS Silicones and CA20PLUS v1.30.23