



NOTE:
SHOWER ROSE IS TO BE FIXED TO WALL

WATER-RESISTANT WALLS TO 1800 FROM FINISHED FLOOR LEVEL
WATERPROOF BATH/WALL JUNCTION

WATERPROOF BATH LIP/TILE JOINT

WATERPROOFING 40mm EITHER SIDE OF JUNCTION

WATERPROOFING

SHOWER ROSE
WATERPROOF CORNER TO 1800 FROM FINISHED FLOOR LEVEL, WIDTH OF 40 EITHER SIDE OF JUNCTION
SEAL TAP, SHOWER ROSE AND BATH SPOUT PENETRATIONS
TAP CONNECTION
WATERPROOFING 40mm EITHER SIDE OF JUNCTION
WATERPROOF TO A MINIMUM OF 1500 FROM SHOWER CONNECTION AT WALL AND GRADE TO A FLOOR WASTE AND TERMINATE WITH A WATERSTOP
WATERPROOF JUNCTION TO 1500 FROM THE SHOWER CONNECTION AT THE WALL AND mm ABOVE FINISHED FLOOR LEVEL

WET AREA WATERPROOFING

NO SHOWER PANEL

SHEET TITLE

DWG NO. **AWW-18**

DATE 03.2026

SCALE 1 : 2 @ A4



Disclaimer: Ardex makes every reasonable effort to ensure that the technical details, recommendations and other information contained in this drawing are accurate and represent our knowledge and experience at the time of design and publication. Ardex reserves the right to change the information without prior notice. Ardex provides the information in good faith with no representations or warranties (whether implied or otherwise), and will not be liable for any losses or damages (whether direct, indirect or consequential) whatsoever, whether in contract, negligence or any other action, arising out of or in connection with the use, or inability to use, the information. It is your responsibility to ensure that our products are used only for the purposes for which they are intended and are used in accordance with any applicable specifications, guidelines, standards, codes of practice, regulations and laws. The supply of our products and services are also subject to certain terms, warranties and exclusions which are available on request.