

ARDEX DS 70

RECYCLED RUBBER IMPACT INSULATION MAT



ARDEX DS 70 is a high-performance, resilient rubber flooring underlayment for the reduction of impact sound, decoupling and crack isolation under hard floorcoverings. ARDEX DS 70 is made from 92% post-consumer recycled, wear- and water-resistant rubber granules and is rated to provide a 14 dB improvement to ISO 717-2. ARDEX DS 70 also acts as a decoupling mat through isolating cracking and substrate movement from the flooring finish.

Use

- Under hard flooring surfaces such as ceramic and stone tiles, luxury vinyl tile and timber
- In both dry and wet areas
- In both commercial and domestic locations
- Internal applications only
- Suitable for use with castor wheels
- Suitable for use with heated floors

Suitable flooring adhesives

- ARDEX AF 145
- ARDEX AF 180 MS
- ARDEX AF 275
- ARDEX AF 2365

Suitable tiling adhesives

- ARDEX X 18
- ARDEX X 52
- ARDEX X 56
- ARDEX X 77

Suitable waterproofing membranes

- ARDEX WPM 155 Rapid
- ARDEX WPM 002

Technical Details

- Weight 45kg
- Colour Black
- Sound reduction ΔL_w 14 dB
- Elongation 50% min.
- Tear strength 205kPa
- Compression at 690kPa 20-30%
- Shore A Hardness 40

Packaging

1.2m x 9.1m x 5mm Roll

Code

20284



To find out more call 0800 227 339
or visit www.ardex.co.nz

