

Ardex ST Silicone Ardex (Ardex NZ)

Chemwatch: **16-4547** Version No: **5.1.1.1** Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017 Chemwatch Hazard Alert Code: 3

Issue Date: 01/11/2019 Print Date: 03/11/2020 S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Ardex ST Silicone
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

al cure silicone for natural stone.
2

Details of the supplier of the safety data sheet

Registered company name	Ardex (Ardex NZ)
Address	32 Lane Street Woolston Christchurch New Zealand
Telephone	+64 3384 3029
Fax	+64 3384 9779
Website	Not Available
Email	Not Available

Emergency telephone number

• • •		
Association / Organisation	Ardex (Ardex NZ)	
Emergency telephone numbers	+64 3 373 6900	
Other emergency telephone numbers	0800 764 766 (NZ NPC)	

SECTION 2 Hazards identification

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

ChemWatch Hazard Ratings

	Min Ma	ax
Flammability	0	
Toxicity	0	0 = Minimum
Body Contact	0	1 = Low
Reactivity	1	2 = Moderate
Chronic	3	3 = High 4 = Extreme

Classification ^[1]	Skin Corrosion/Irritation Category 3	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	6.3B	

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Warning

Hazard statement(s)

H316 Causes mild skin irritation.

Precautionary statement(s) Prevention Not Applicable Precautionary statement(s) Response P332+P313 If skin irritation occurs: Get medical advice/attention. Precautionary statement(s) Storage Not Applicable Precautionary statement(s) Disposal Not Applicable SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
2224-33-1	<5	vinyltris(methylethylketoxime)silane
2768-02-7	<2.5	trimethoxyvinylsilane
128446-60-6	<2.5	silsesquioxanes, 3-aminopropyl Me, ethoxy terminated

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	+ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. 		
Fire/Explosion Hazard	carbon dioxide (CO2) silicon dioxide (SiO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes. Non combustible. Not considered to be a significant fire risk. Expansion or decomposition on heating may lead to violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). Other decomposition products include:		

SECTION 6 Accidental release measures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	Material name		TEEL-1	TEEL-2	TEEL-3
trimethoxyvinylsilane	rimethoxyvinylsilane Trimethoxyvinylsilane; (Vinyltrimethoxysilane; Silane, trimethoxyvinyl-)		9.5 ppm	100 ppm	120 ppm
Ingredient	Original IDLH	Revised IDLH			
vinyltris(methylethylketoxime)silane	Not Available	Not Available			
trimethoxyvinylsilane	Not Available	Not Available			
silsesquioxanes, 3-aminopropyl Me, ethoxy terminated	Not Available	Not Available			

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating Occupational Exposure Band Limit	
vinyltris(methylethylketoxime)silane	D	> 0.1 to ≤ 1 ppm
trimethoxyvinylsilane	E	≤ 0.1 ppm
silsesquioxanes, 3-aminopropyl Me, ethoxy terminated	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.	
Appropriate engineering	The basic types of engineering controls are:	
controls	Process controls which involve changing the way a job activity or process is done to reduce the risk.	
	Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically	
	"adds" and "removes" air in the work environment.	

Personal protection		
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describin the wearing of lenses or restrictions on use, should be created for each workplace or task. 	
Skin protection	See Hand protection below	
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. 	
Body protection	See Other protection below	
Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. 	

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1	-
up to 50	1000	-	A-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	A-2
up to 100	10000	-	A-3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Transparent or tinted paste with an intense odour; does not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	1.03 approx.
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	430 approx.
pH (as supplied)	7	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available

Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7		
Chemical stability	Chemical stability Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 		
Possibility of hazardous reactions	See section 7		
Conditions to avoid	See section 7		
Incompatible materials	ee section 7		
Hazardous decomposition products	See section 5		

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The major toxic effects of MEKO, regardless of the route of administration, are anaemia with breakdown of red blood cells, rapid breathing and reversible reduction in spontaneous activity, motor coordination and muscle tone. At extremely high concentrations it may cause unconsciousness and failure of breathing.			
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.			
Skin Contact	The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. Skin application with methyl ethyl ketoxime under an occlusive dressing produced mild irritation with redness, swelling and wheals. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). 0.1 ml of methyl ethyl ketoxime can be corrosive to the eye.			
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Methyl ethyl ketoxime causes an immediate but transient central nervous system depression, dose-related decreases in red blood cell counts accompanied by a compensatory marked increase in number of immature red cells, suggesting rapid red cell breakdown. Other effects include dose-related increase in spleen, liver and kidney weights. Deposits of iron have been reported in the liver and spleen at repeated high doses. This may increase risk of liver tumours. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.			

	ΤΟΧΙΟΙΤΥ	IRRITATION	
Ardex ST Silicone	Not Available	Not Available	
	тохісіту	IRRITATION	
vinyltris(methylethylketoxime)silane	Not Available	Eye: adverse effect observed (irritating) ^[1]	
		Skin: no adverse effect observed (not irritating) $\left[1 \right]$	
	тохісіту	IRRITATION	
	Inhalation (rat) LC50: 17 mg/l/4hours] ^[2]	Eye (rabbit): 500 mg/24h - mild	
	Oral (rat) LD50: >300-2000 mg/kg ^[1]	Eye (rabbit): 500 mg/24h mild	
trimethoxyvinylsilane		Eye: no adverse effect observed (not irritating) ^[1]	
		Skin (rabbit): 500 mg/24h - mild	
		Skin (rabbit): 500 mg/24h mild	
		Skin: no adverse effect observed (not irritating) $\left[1 \right]$	
silsesquioxanes, 3-aminopropyl Me,	ΤΟΧΙΟΙΤΥ	IRRITATION	
ethoxy terminated	Not Available	Not Available	
	Alue obtained from Europe ECHA Registered Substances - Acute toxic cified data extracted from RTECS - Register of Toxic Effect of chemica		

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic VINYLTRIS(METHYLETHYLKETOXIME)SILANE skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are

		equally important. No significant acute toxicological data identified in literature search. alpha,beta-Unsaturated oximes represent two previously unknown classes of prohaptens.Three putative metabolites were proposed as sensitising agents. These included two diastereometric alpha,beta-epoxy oximes and a nitro analogue. When tested in the LLNA,alpha,beta-epoxy oximes. Allergic Contact Dermatitis—Formation, Structural Requirements,and Reactivity of Skin Sensitizers. Ann-Therese Karlberg et al: Chem. Res.	
TRIMETHOXYVINYLSILANE		Ann-Therese Karlberg et al: Chem. Res. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. Low molecular weight alkoxysilane can cause irreversible lung damage when inhaled at low dose. It is not an obvious skin irritant. However, studies suggest with repeated occupational exposure, methoxysilane may cause damage to the eye and skin as well as cancer. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Manufacturers Data:	
VINYLTRIS(METHYLETHYLKETOXIME)SILANE & TRIMETHOXYVINYLSILANE		The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.	
Acute Toxicity	(Carcinogenicity	

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
		Legend: 🛛 🗙 – Data either no	t available or does not fill the criteria for classification

Data entrer not available of does not Data available to make classification

SECTION 12 Ecological information

	Endpoint	Test Duration (hr)	Species	Value	Source
Ardex ST Silicone	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	1-11.11mg/L	2
vinyltris(methylethylketoxime)silane	EC50	48	Crustacea	>120mg/L	2
	EC50	96	Algae or other aquatic plants	1-429mg/L	2
	NOEC	72	Algae or other aquatic plants	1mg/L	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>1-mg/L	2
trimethoxyvinylsilane	EC50	48	Crustacea	>100mg/L	2
	EC50	72	Algae or other aquatic plants	>89mg/L	2
	NOEC	168	Algae or other aquatic plants	>=1-mg/L	2
	Endpoint	Test Duration (hr)	Species	Value	Source
silsesquioxanes, 3-aminopropyl Me, ethoxy terminated	Not Available	Not Available	Not Available	Not Available	Not Available

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Legend: Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability Ingredient Persistence: Water/Soil

Ingredient	Persistence: Water/Soil	Persistence: Air
trimethoxyvinylsilane	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
trimethoxyvinylsilane	LOW (LogKOW = -0.3169)

Mobility in soil

Ingredient	Mobility
trimethoxyvinylsilane	LOW (KOC = 757.6)

Ardex ST Silicone

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. D NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002624	N.O.S. (Subsidiary Hazard) Group Standard 2017
HSR002535	Gas Under Pressure Mixtures (Subsidiary Hazard) Group Standard 2017
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2017
HSR002530	Cleaning Products (Subsidiary Hazard) Group Standard 2017
HSR002585	Fuel Additives (Subsidiary Hazard) Group Standard 2017
HSR002519	Aerosols (Subsidiary Hazard) Group Standard 2017
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2017
HSR002606	Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2017
HSR002644	Polymers (Subsidiary Hazard) Group Standard 2017
HSR002647	Reagent Kits Group Standard 2017
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017
HSR002638	Photographic Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002565	Embalming Products (Subsidiary Hazard) Group Standard 2017
HSR002578	Food Additives and Fragrance Materials (Subsidiary Hazard) Group Standard 2017
HSR002558	Dental Products (Subsidiary Hazard) Group Standard 2017
HSR002684	Water Treatment Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002573	Fire Fighting Chemicals Group Standard 2017
HSR100425	Pharmaceutical Active Ingredients Group Standard 2017
HSR002600	Leather and Textile Products (Subsidiary Hazard) Group Standard 2017

Ardex ST Silicone

HSR Number	Group Standard
HSR002605	Lubricants (Low Hazard) Group Standard 2017
HSR002571	Fertilisers (Subsidiary Hazard) Group Standard 2017
HSR002648	Refining Catalysts Group Standard 2017
HSR002653	Solvents (Subsidiary Hazard) Group Standard 2017
HSR002544	Construction Products (Subsidiary Hazard) Group Standard 2017
HSR002549	Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2017
HSR100757	Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2017
HSR100758	Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2017
HSR100759	Veterinary Medicines (Non-dispersive Open System Application) Group Standard 2017
HSR100580	Tattoo and Permanent Makeup Substances Group Standard 2017
HSR002612	Metal Industry Products (Subsidiary Hazard) Group Standard 2017
HSR002503	Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2017
HSR002552	Cosmetic Products Group Standard 2017

vinyltris(methylethylketoxime)silane is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

trimethoxyvinylsilane is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data New Zealand Inventory of Chemicals (NZIoC)

silsesquioxanes, 3-aminopropyl Me, ethoxy terminated is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC	Yes
Australia - Non-Industrial Use	No (vinyltris(methylethylketoxime)silane; trimethoxyvinylsilane; silsesquioxanes, 3-aminopropyl Me, ethoxy terminated)
Canada - DSL	No (silsesquioxanes, 3-aminopropyl Me, ethoxy terminated)
Canada - NDSL	No (vinyltris(methylethylketoxime)silane; trimethoxyvinylsilane; silsesquioxanes, 3-aminopropyl Me, ethoxy terminated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (silsesquioxanes, 3-aminopropyl Me, ethoxy terminated)
Japan - ENCS	No (silsesquioxanes, 3-aminopropyl Me, ethoxy terminated)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (vinyltris(methylethylketoxime)silane; trimethoxyvinylsilane; silsesquioxanes, 3-aminopropyl Me, ethoxy terminated)
Vietnam - NCI	Yes
Russia - ARIPS	No (silsesquioxanes, 3-aminopropyl Me, ethoxy terminated)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	01/11/2019
Initial Date	18/09/2008

SDS Version Summary

Version	Issue Date	Sections Updated
3.1.1.1	19/11/2013	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Chronic Health, Disposal, Engineering Control, Fire Fighter (fire/explosion hazard), Fire Fighter (fire incompatibility), Ingredients, Storage (storage incompatibility)
5.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

