

ARDEX TILING PRODUCT SELECTOR



ARDEX PRODUCT	CERAMIC TILES					NATURAL STONE TILES (SEE TECHNICAL BULLETIN 010 AND/OR 143)				SUBSTRATES													
	Highly Porous Terracotta (3-6% WA)	Porous Monocottura (1.5-6%)	Porous Ceramic Mosaic (<1.5%)	Low Porosity Glass Mosaic (<1.5%)	Low Porosity Vitrified/Porcelain (<1.5%)	Nonsensitive Natural Stone	Translucent Marble	Green Marble	Slate	Render	Concrete	Heated Concrete	Sand/Cement Screed	Existing Tiles	Fibre-Cement Medium Density	Compressed Fibre-Cement Sheet	Timber Internal	Plasterboard	Swimming Pools	Fibreglass & Butynol®	Undertile Membrane	Floors	Walls
ARDEX X 77	●	●	●	●	●	●			●	●	●	●	●	(I)	●	●		●	●		●	●	●
ARDEX X 78	●	●	●	●	●	●			●					(I)									
ARDEX ABAFLEX	●	●	●	●	●	●			●					(G)	(W)								
ARDEX S 28 NEU	●	●	●	●	●	●	●	●	●	(D,I)	(D,I)	(D,I)	(D,I)	(D,I)	(A,D,I)	(A,D,I)		(A,D,I)				(D,I)	(D,I)
ARDEX X 56	●	●	●	●	●	●			●								(P)						
ARDEX X 52	●	●	●	●	●	●			●					(G)	(W)								
ARDEX X 18	●	●	●	●	●	●			●					(I)	(P,W)	(I)		(P,W)					
ARDEX X 10	●	●	●	●	●	●			●					(G)	(W)								
ARDEX QUICKBOND	●	●	●	●	●	●			●			(A)		(G)	(A,W)	(A)		(A)					
ARDEX D 2	●	●	●	●	●	●			●						(W)								
ARDEX WA 100	●	●	●	●	●	●	●	●	●														
ARDEX OPTIMA	●	●	●	●	●	●	●	●	●					(G)									
ARDEX MPP	●	●	●	●	●	●	●	●	●						(W)								

Refer to Technical Bulletin 010 & 001 for special recommendations in dealing with moisture sensitive stones. For other applications not listed, please contact ARDEX Technical Services.

DISCLAIMER: The technical details, recommendations and other information contained in this sheet are given in good faith and represent the best of our knowledge and experience at the time of issue. It is your responsibility to ensure that our products are used and handled correctly and in accordance with an applicable New Zealand Standard, our instructions and recommendations and only for the users are they intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, Codes of Practice, Building Regulations or Industry Guidelines, may effect specific installation recommendations. This guide is intended as a quick reference selector only, please always refer to the relevant product datasheets for specific instructions. ARDEX makes no claim on tile performance in the above situation, please refer to the tile manufacturer to ensure the tile is suitable for the application intended.

KEY

- (W) Walls only
- (G) Glaze removed
- (D) Dry area only
- (P) Prime with Optima/P9
- (A) Additive required see packaging
- (I) Internal only

0800 2 ARDEX
www.ardex.co.nz