

Ardex (Ardex NZ)

Chemwatch: 5368-25 Version No: 2.1.1.1 Safety Data Sheet according to HSNO Regulations

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	ARDEX WPM 400 Primer Part A
Synonyms	Not Available
Other means of identification	Not Available
Relevant identified uses of the substance or mixture and uses advised against	

## 

Relevant identified uses	Professional use, substrate preparation.

#### Details of the supplier of the safety data sheet

Registered company name	Ardex (Ardex NZ)
Address	32 Lane Street Woolston Christchurch New Zealand
Telephone	+64 3384 3029
Fax	+64 3384 9779
Website	Not Available
Email	Not Available

## Emergency telephone number

Association / Organisation	Ardex (Ardex NZ)
Emergency telephone numbers	+64 3 373 6900
Other emergency telephone numbers	Not Available

# **SECTION 2 HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

#### CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	1		
Toxicity	1		0 = Minimum
Body Contact	3		1 = Low 2 = Moderate
Reactivity	1		3 = High
Chronic	3		4 = Extreme

Classification <sup>[1]</sup>	Acute Toxicity (Inhalation) Category 5, Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Reproductive Toxicity Category 1, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.1E (inhalation), 6.3A, 6.5B (contact), 6.8A, 8.3A, 9.1C

## Label elements

Hazard pictogram(s)



Chemwatch Hazard Alert Code: 3 Issue Date: 02/09/2019 Print Date: 23/09/2019 S.GHS.NZL.EN

SIGNAL WORD	DANGER	
Hazard statement(s)		
H333	May be harmful if inhaled.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H317	May cause an allergic skin reaction.	
H360	May damage fertility or the unborn child.	
H412	Harmful to aquatic life with long lasting effects.	
Precautionary statement(s) Pr	revention	
P201	Obtain special instructions before use.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P261	Avoid breathing mist/vapours/spray.	
P273	Avoid release to the environment.	

## Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P321	Specific treatment (see advice on this label).	
P321	Specific treatment (see advice on this label).	

# Precautionary statement(s) Storage

P405 Store locked up.

# Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

# SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

# Mixtures

%[weight]	Name
20-30	linseed oil/ BADGE/ formaldehyde/ diethylenetriamine polymer
<0.6	pentaethylenehexamine
<0.6	acetic acid glacial
<0.6	tetraethylenepentamine
<0.6	diethylenetriamine
	20-30 <0.6 <0.6 <0.6

# SECTION 4 FIRST AID MEASURES

## Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>Transport to hospital or doctor without delay.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	If skin contact occurs: <ul> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# SECTION 5 FIREFIGHTING MEASURES

#### Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).

# Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Advice for firefighters			
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>		
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>Combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>nitrogen oxides (NOx)</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit corrosive fumes.</li> </ul>		

## SECTION 6 ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# SECTION 7 HANDLING AND STORAGE

## Precautions for safe handling

Safe handling	<ul> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>
Conditions for safe storage,	including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	<ul> <li>Avoid cross contamination between the two liquid parts of product (kit).</li> <li>If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur.</li> <li>This excess heat may generate toxic vapour</li> <li>Avoid reaction with amines, mercaptans, strong acids and oxidising agents</li> </ul>

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Control parameters**

# INGREDIENT DATA

INGREDIENT DATA								
Source	Ingredient	Material name	TWA	STEL		Peak	Notes	
New Zealand Workplace Exposure Standards (WES)	acetic acid glacial	Acetic acid	10 ppm / 25 mg/m3	37 mg/	m3 / 15 ppm	Not Available	Not Available	
New Zealand Workplace Exposure Standards (WES)	diethylenetriamine	Diethylene triamine	1 ppm / 4.2 mg/m3	Not Available		Not Available	(skin) - Skin absorption	
EMERGENCY LIMITS								
Ingredient	Material name		TEEL-1	TEEL-2			TEEL-3	
acetic acid glacial	Acetic acid		Not Available		Not Available		Not Available	
tetraethylenepentamine	Tetraethylenepentamine		15 mg/m3		130 mg/m3		790 mg/m3	
diethylenetriamine	Diethylenetriamine		3 ppm	8.5 ppm		51 ppm		
Ingredient	Original IDLH			Revise	d IDLH			
linseed oil/ BADGE/ formaldehyde/ diethylenetriamine polymer	Not Available		Not Ava	ilable				
pentaethylenehexamine	Not Available			Not Available				

Not Available

Not Available

Not Available

## Exposure controls

acetic acid glacial

diethylenetriamine

tetraethylenepentamine

50 ppm

Not Available

Not Available

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	<ul> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	NOTE:         • The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.         • Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.         The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.         Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.         The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.         Personal hygiene is a key element of effective hand care.         When handling liquid-grade epoxy resins wear chemically protective gloves , boots and aprons.         The performance, based on breakthrough times ,of:         • Ethyl Winyl Alcohol (EVAL laminate) is generally excellent         • Buyl Rubber (NBR) from excellent to fair.         • Neoprene from excellent to poor         As defined in ASTM F-739-96         • Excellent breakthrough time > 20 min         • Fair breakthrough time > 20 min         • Fair breakthrough time > 20 min         • Poor glove material degradation         Gloves should be tested against each resin system prior to making a selection of the most suitable type. Systems include both the resin
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C. apron.</li> <li>Barrier cream.</li> </ul>

## Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

#### **Respiratory protection**

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered

#### ARDEX WPM 400 Primer Part A

Material	CPI
BUTYL	A
NEOPRENE	A
BUTYL/NEOPRENE	С
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PE	С
PE/EVAL/PE	С
PVC	С
SARANEX-23	С
TEFLON	С
VITON	С

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Appearance	Amber coloured liquid; partly mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	1-1.4
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	9.25	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	3166.7-3833.3
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>100 (PMCC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# SECTION 11 TOXICOLOGICAL INFORMATION

## appropriate.

 Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Inhaled	• ·	r irritation of the respiratory tract (as classified by EC Directives using animal models). kept to a minimum and that suitable control measures be used in an occupational setting.			
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.				
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.				
Eye	If applied to the eyes, this material causes severe eye damage.				
Chronic	Ample evidence exists, from results in experimentation, that deve	ion reaction in some persons compared to the general population. elopmental disorders are directly caused by human exposure to the material. er or mutations but there is not enough data to make an assessment.			
	TOXICITY	IRRITATION			
ARDEX WPM 400 Primer Part A	Not Available Not Available				
linseed oil/ BADGE/	ΤΟΧΙΟΙΤΥ	IRRITATION			
formaldehyde/ diethylenetriamine polymer	Not Available	Not Available			
pentaethylenehexamine					
	Oral (rat) LD50: 1591.4 mg/kg <sup>[1]</sup>	Not Available			
	TOXICITY	IRRITATION			
	Dermal (rabbit) LD50: 1060 mg/kg <sup>[2]</sup>	Eye (rabbit): 0.05mg (open)-SEVERE			
acetic acid glacial	Inhalation (rat) LC50: 11 mg/l/4H <sup>[2]</sup>	Skin (human):50mg/24hr - mild			
	Oral (rat) LD50: 3310 mg/kg <sup>[2]</sup>	Skin (rabbit):525mg (open)-SEVERE			
	ΤΟΧΙΟΙΤΥ	IRRITATION			
	Dermal (rabbit) LD50: 658.68 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg/24h moderate			
tetraethylenepentamine	Oral (rat) LD50: =2100 mg/kg <sup>[2]</sup>	Eye (rabbit): 5 mg moderate			
		Skin (rabbit): 495 mg SEVERE			
		Skin (rabbit): 5 mg/24h SEVERE			
	ΤΟΧΙΟΙΤΥ	IRRITATION			
	Dermal (rabbit) LD50: ~672 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>			
diethylenetriamine	Oral (rat) LD50: =819-1430 mg/kg <sup>[2]</sup>	Skin (rabbit): 10 mg/24h - SEVERE			
		Skin (rabbit):500 mg open moderate			
		Skin: adverse effect observed (corrosive) <sup>[1]</sup>			
Legend:	<ol> <li>Value obtained from Europe ECHA Registered Substances - data extracted from RTECS - Register of Toxic Effect of chemic</li> </ol>	Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified al Substances			
LINSEED OIL/ BADGE/ FORMALDEHYDE/ DIETHYLENETRIAMINE POLYMER	No significant acute toxicological data identified in literature search. Animal testing over 13 weeks showed bisphenol A diglycidyl ether (BADGE) caused mild to moderate, chronic, inflammation of the skin. Reproductive and Developmental Toxicity: Animal testing showed BADGE given over several months caused reduction in body weight but had no reproductive effects. Cancer-causing potential: It has been concluded that bisphenol A diglycidyl ether cannot be classified with respect to its cancer-causing potential in humans. Genetic toxicity: Laboratory tests on genetic toxicity of BADGE have so far been negative. Bisphenol A diglycidyl ethers (BADGEs) produce a sensitization dermatitis (skin inflammation) characterized by eczema with blisters and papules, with considerable itching of the back of the hand. This may persist for 10-14 days after withdrawal from exposure and recur immediately on re-exposure. The dermatitis may last longer following each exposure, but is unlikely to become more intense. Lower molecular weight species produce sensitization more readily. Bisphenol A may have effects similar to female sex hormones and when administered to pregnant women, may damage the foetus. It may also damage male reproductive organs and sperm. Glycidyl ethers can cause genetic damage and cancer.				
PENTAETHYLENEHEXAMINE	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Overexposure to most of these materials may cause adverse health effects. Many amine-based compounds can cause release of histamines, which, in turn, can trigger allergic and other physiological effects, including constriction of the bronchi or asthma and inflammation of the cavity of the nose. Whole-body symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, rapid heartbeat, itching, reddening of the skin, urticaria (hives) and swelling of the face, which are usually transient. There are generally four routes of possible or potential exposure: inhalation, skin contact, eye contact, and swallowing. Pentaethylenehexamine has not been evaluated in mammals with respect to its ability to cause genetic toxicity; limited testing with structurally related polyamines show that they do not produce tumours. Pentaethylenehexamine causes increased secretion of certain metals, including copper and cadmium, in rats.				

ACETIC ACID GLACIAL	examined in this respect. Mucous secretion may protect the stomach lining from the hydrochloric acid secreted there, Prolonged or repeated exposure to acetic acid may produce inhalation exposure results in muscle imbalance, increase or foetal toxicity, according to animal testing. The material may produce moderate eye irritation leading	). uce irritation and/ or corrosion at the site se in blood cholinesterase activity, decrea to inflammation. Repeated or prolongec	of contact as well as systemic toxicity. Prolonged ase in albumin and decreased growth but no reproductive lexposure to irritants may produce conjunctivitis.	
TETRAETHYLENEPENTAMINE	Triethylenetetramine is a severe irritant to skin and eyes and may induce skin sensitisation. Acute exposure to saturated vapour via inhalation was tolerated without impairment but exposure to aerosol may lead to reversible irritations of the mucous membranes in the airways. Studies done on experimental animals showed that it does not cause cancer or foetal developmental defects. Tetraethylenepentamine (TEPA) has a low acute toxicity when taken orally and a higher toxicity via the dermal route most likely due to the corrosive nature of TEPA to the skin against neutralization by stomach acid. TEPA may be corrosive to the skin and eyes. Long term dermal application may cause thickening of the epidermis and other skin changes. There were no evidence of reproductive toxicity but there may be foetal toxicity at high doses most likely due to copper deficiency and zinc toxicity.			
DIETHYLENETRIAMINE	Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins. Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.			
LINSEED OIL/ BADGE/ FORMALDEHYDE/ DIETHYLENETRIAMINE POLYMER & PENTAETHYLENEHEXAMINE & TETRAETHYLENEPENTAMINE & DIETHYLENETRIAMINE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.			
PENTAETHYLENEHEXAMINE & ACETIC ACID GLACIAL & TETRAETHYLENEPENTAMINE & DIETHYLENETRIAMINE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.			
PENTAETHYLENEHEXAMINE & TETRAETHYLENEPENTAMINE & DIETHYLENETRIAMINE	Ethyleneamines are very reactive and can cause chemical burns, skin rashes and asthma-like symptoms. It is readily absorbed through the skin and may cause eye blindness and irreparable damage. As such, they require careful handling. In general, the low-molecular weight polyamines have been positive in the Ames assay (for genetic damage); however, this is probably due to their ability to chelate copper. For alkyl polyamines: The alkyl polyamines cluster consists of two terminal primary and at least one secondary amine groups and are derivatives of low molecular weight ethylenediamine, propylenediamine or hexanediamine. Toxicity depends on route of exposure. Cluster members have been shown to cause skin irritation or sensitisation, eye irritation and genetic defects, but have not been shown to cause cancer.			
ACETIC ACID GLACIAL & DIETHYLENETRIAMINE	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.			
ACETIC ACID GLACIAL &	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.			
TETRAETHYLENEPENTAMINE & DIETHYLENETRIAMINE	<u> </u>			
	<b>✓</b>	Carcinogenicity	×	
& DIETHYLENETRIAMINE	* *	Carcinogenicity Reproductivity	× •	
& DIETHYLENETRIAMINE				
& DIETHYLENETRIAMINE Acute Toxicity Skin Irritation/Corrosion		Reproductivity	×	

# SECTION 12 ECOLOGICAL INFORMATION

# Toxicity

ARDEX WPM 400 Primer Part A	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
linseed oil/ BADGE/	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
formaldehyde/ diethylenetriamine polymer	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	180.00mg/L	2
pentaethylenehexamine	EC50	48	Crustacea	17.5mg/L	2
	EC50	72	Algae or other aquatic plants	0.7mg/L	2
	NOEC	72	Algae or other aquatic plants	0.25mg/L	2
acetic acid glacial	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-mg/L	2

	EC50	48	Crustacea	>1-mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	NOEC	72	Algae or other aquatic plants	1-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	105000mg/L	3
tetraethylenepentamine	EC50	48	Crustacea	=24.1mg/L	1
	EC50	72	Algae or other aquatic plants	=2.1mg/L	1
	NOEC	72	Algae or other aquatic plants	=0.5mg/L	1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	1-14mg/L	2
diethylenetriamine	EC50	48	Crustacea	=16mg/L	1
	EC50	72	Algae or other aquatic plants	1-164mg/L	2
	NOEC	504	Crustacea	=5.6mg/L	1
Legend:	(QSAR) - Aquat	. IUCLID Toxicity Data 2. Europe ECHA Register ic Toxicity Data (Estimated) 4. US EPA, Ecotox d icentration Data 7. METI (Japan) - Bioconcentrati	atabase - Aquatic Toxicity Data 5. ECETOC Aqu		

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **DO NOT** discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
pentaethylenehexamine	LOW	LOW
acetic acid glacial	LOW	LOW
tetraethylenepentamine	LOW	LOW
diethylenetriamine	LOW	LOW

## **Bioaccumulative potential**

Ingredient	Bioaccumulation
pentaethylenehexamine	LOW (LogKOW = -3.6744)
acetic acid glacial	LOW (LogKOW = -0.17)
tetraethylenepentamine	LOW (LogKOW = -3.1604)
diethylenetriamine	LOW (BCF = 1.7)

## Mobility in soil

Ingredient	Mobility
pentaethylenehexamine	LOW (KOC = 3887)
acetic acid glacial	HIGH (KOC = 1)
tetraethylenepentamine	LOW (KOC = 1098)
diethylenetriamine	LOW (KOC = 87.53)

#### SECTION 13 DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Product / Packaging disposal	<ul> <li>Waste Management</li> <li>Production waste from epoxy resins and resin systems should be treated as hazardous waste in accordance with National regulations. Fire retarded resins containing halogenated compounds should also be treated as special waste. Accidental spillage of resins, curing agents and their formulations should be contained and absorbed by special mineral absorbents to prevent them from entering the environment.</li> <li>Contaminated or surplus product should not be washed down the sink, but preferably be fully reacted to form cross-linked solids which is non-hazardous and can be more easily disposed.</li> <li><b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Authority for disposal.</li> <li>Bury or incinerate residue at an approved site.</li> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
------------------------------	---

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

## **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and

#### removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

#### **SECTION 14 TRANSPORT INFORMATION**

Labels Required	
Marine Pollutant	NO
HAZCHEM	Not Applicable

# Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## **SECTION 15 REGULATORY INFORMATION**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002624	N.O.S. (Subsidiary Hazard) Group Standard 2017
HSR002535	Gas Under Pressure Mixtures (Subsidiary Hazard) Group Standard 2017
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2017
HSR002530	Cleaning Products (Subsidiary Hazard) Group Standard 2017
HSR002585	Fuel Additives (Subsidiary Hazard) Group Standard 2017
HSR002519	Aerosols (Subsidiary Hazard) Group Standard 2017
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2017
HSR002606	Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2017
HSR002644	Polymers (Subsidiary Hazard) Group Standard 2017
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017
HSR002638	Photographic Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002565	Embalming Products (Subsidiary Hazard) Group Standard 2017
HSR002558	Dental Products (Subsidiary Hazard) Group Standard 2017
HSR002684	Water Treatment Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002573	Fire Fighting Chemicals Group Standard 2017
HSR100425	Pharmaceutical Active Ingredients Group Standard 2017
HSR002600	Leather and Textile Products (Subsidiary Hazard) Group Standard 2017
HSR002571	Fertilisers (Subsidiary Hazard) Group Standard 2017
HSR002648	Refining Catalysts Group Standard 2017
HSR002653	Solvents (Subsidiary Hazard) Group Standard 2017
HSR002544	Construction Products (Subsidiary Hazard) Group Standard 2017
HSR002549	Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2017
HSR100757	Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2017
HSR100758	Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2017
HSR100759	Veterinary Medicines (Non-dispersive Open System Application) Group Standard 2017
HSR002612	Metal Industry Products (Subsidiary Hazard) Group Standard 2017
HSR002503	Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2017

## LINSEED OIL/ BADGE/ FORMALDEHYDE/ DIETHYLENETRIAMINE POLYMER IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

# PENTAETHYLENEHEXAMINE IS FOUND ON THE FOLLOWING REGULATORY LISTS

GESAMP/EHS Composite List - GESAMP Hazard Profiles	International Maritime Dangerous Goods Requirements (IMDG Code)
IMO IBC Code Chapter 17: Summary of minimum requirements	New Zealand Inventory of Chemicals (NZIoC)
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
International Air Transport Association (IATA) Dangerous Goods Regulations	

ACETIC ACID GLACIAL IS FOUND ON THE FOLLOWING REGULATORY LISTS

GESAMP/EHS Composite List - GESAMP Hazard Profiles	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of
IMO IBC Code Chapter 17: Summary of minimum requirements	Chemicals
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures	
containing at least 99% by weight of components already assessed by IMO, presenting safety	New Zealand Inventory of Chemicals (NZIoC)
hazards	New Zealand Workplace Exposure Standards (WES)
International Air Transport Association (IATA) Dangerous Goods Regulations	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
International Maritime Dangerous Goods Requirements (IMDG Code)	
TETRAETHYLENEPENTAMINE IS FOUND ON THE FOLLOWING REGULATORY LISTS	
GESAMP/EHS Composite List - GESAMP Hazard Profiles	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of
IMO IBC Code Chapter 17: Summary of minimum requirements	Chemicals
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of
International Air Transport Association (IATA) Dangerous Goods Regulations	Chemicals - Classification Data
International Maritime Dangerous Goods Requirements (IMDG Code)	New Zealand Inventory of Chemicals (NZIoC)
	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
DIETHYLENETRIAMINE IS FOUND ON THE FOLLOWING REGULATORY LISTS	
GESAMP/EHS Composite List - GESAMP Hazard Profiles	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of
IMO IBC Code Chapter 17: Summary of minimum requirements	Chemicals
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of
International Air Transport Association (IATA) Dangerous Goods Regulations	Chemicals - Classification Data
International FOSFA List of Banned Immediate Previous Cargoes	New Zealand Inventory of Chemicals (NZIoC)
International Maritime Dangerous Goods Requirements (IMDG Code)	New Zealand Workplace Exposure Standards (WES)
	United Nationa Recommandations on the Transport of Dangerous Coode Model Regulations

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

# Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

# **Tracking Requirements**

Not Applicable

#### **National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (pentaethylenehexamine; tetraethylenepentamine; linseed oil/ BADGE/ formaldehyde/ diethylenetriamine polymer; acetic acid glacial; diethylenetriamine)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (linseed oil/ BADGE/ formaldehyde/ diethylenetriamine polymer)
Japan - ENCS	No (linseed oil/ BADGE/ formaldehyde/ diethylenetriamine polymer)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (pentaethylenehexamine; linseed oil/ BADGE/ formaldehyde/ diethylenetriamine polymer)
Vietnam - NCI	Yes
Russia - ARIPS	No (linseed oil/ BADGE/ formaldehyde/ diethylenetriamine polymer)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

# **SECTION 16 OTHER INFORMATION**

Revision Date	02/09/2019
Initial Date	27/08/2019

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

end of SDS

# ARDEX WPM 400 Primer Part A

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL : No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.